

Building series


clase energética A

Excepto HSU-22HA03/R2(DB)



9K, 12K, 18K

HSU-09HA103/R2(DB) 599 €
 HSU-12HA103/R2(DB) 649 €
 HSU-18HA103/R2(DB) 1.059 €
 HSU-22HA103/R2(DB) 1.199 €



DC Inverter

MODELO			HSU-09HA103/R2(DB)	HSU-12HA103/R2(DB)	HSU-18HA103/R2(DB)	HSU-22HA103/R2(DB)
Capacidad nominal	Enfriamiento	Kw (min-max)	2,62 (1,20-3,50)	3,50 (1,80-4,30)	5,00 (1,85-5,50)	5,80 (1,85-6,30)
		Frig/h (min-max)	2.261 (1.032-3.010)	3.010 (1.548-3.870)	4.300 (1.650-4.730)	4.988 (1.591-5.418)
	Calefacción	Kw (min-max)	3,32 (1,00-4,00)	3,86 (1,80-4,50)	5,50 (1,85-6,00)	6,20 (1,85-6,80)
		Kcal/h(min-max)	2.855 (860-3.440)	3.319 (1.548-3.870)	4.730 (1.650-5.160)	5.332 (1.591-5.848)
Potencia consumida	Enfriamiento	Kw (min-max)	0,82 (0,28-1,25)	1,09 (0,35-1,55)	1,56 (0,47-1,95)	1,92 (0,31-2,45)
	Calefacción	Kw (min-max)	0,92 (0,27-1,25)	1,07 (0,35-1,52)	1,71 (0,55-2,20)	2,05 (0,45-2,65)
Clase energética	Enfriamiento (EER)	Kw/Kw	3,21 (A)	3,21 (A)	3,21 (A)	3,02 (B)
	Calefacción (COP)	Kw/Kw	3,61 (A)	3,61 (A)	3,22 (C)	3,02 (D)
Intensidad absorbida	Enfriamiento	A	3,9(1,3-5,8)	4,9(2,1-7,0)	6,9(1,2-8,5)	8,5(1,3-10,6)
	Calefacción	A	4,6(1,3-5,8)	4,8(2,0-6,9)	7,6(2,5-9,6)	9,1(1,9-11,5)
Máxima Intesidad absorbida		A	5,8	7	9,6	11,5
Alimentación eléctrica		(Ph/V/Hz)	(1/230/50)	(1/230/50)	(1/230/50)	(1/230/50)
Interconexión eléctrica		mm ²	U.I (2x2,5+T)	U.I (2x2,5+T)	U.E (2x2,5+T)	U.E (2x2,5+T)
Intercon/i3n de Control		mm ²	(4x1,5)	(4x1,5)	(4x1,5)	(4x1,5)
Caudal de aire		m ³ /h	450	500	660	660
Refrigerante			R410A			
Diámetro de tuberías	gas	mm	9,53 (3/8")	9,53 (3/8")	12,70 (1/2")	12,70 (1/2")
	líquido	mm	6,35 (1/4")	6,35 (1/4")	6,35 (1/4")	6,35 (1/4")
Distancia Máxima Total (Vertical)		m	15(10)	15(10)	25(15)	25(15)
Precarga		m	7	7	7	7
Carga adicional		g/m	20	20	20	20
Rango de Temperatura	Enfriamiento	°C	18-43°C	18-43°C	18-43°C	18-43°C
	Calefacción	°C	-7-27°C	-7-27°C	-7-27°C	-7-27°C
Unidad Interior						
Dimensiones netas	(Ancho/Fondo/Alto)	mm	(795/182/265)	(795/182/265)	(938/255/643)	(938/255/643)
Dimensiones con embalaje	(Ancho/Fondo/Alto)	mm	(863/275/330)	(863/275/330)	(990/275/300)	(990/275/300)
Peso neto		Kg	7,6	7,6	10,6	10,6
Peso bruto		Kg	9,3	9,3	12,6	12,6
Nivel sonoro	(Alto/Nominal/Bajo)	dB(A)	40/36/34	41/38/36	46/42/38	46/44/40
Unidad Exterior						
Dimensiones netas	(Ancho/Fondo/Alto)	mm	(783/255/543)	(783/255/543)	(783/255/543)	(820/310/682)
Dimensiones con embalaje	(Ancho/Fondo/Alto)	mm	(930/340/620)	(930/300/620)	(990/340/714)	(949/406/745)
Peso neto		Kg	31,5	38	39	43
Peso bruto		Kg	34,5	42	43	48
Nivel sonoro		dB(A)	55	55	56	56